

Microbiology Research Journal International

20(4): 1-6, 2017; Article no.MRJI.26264

ISSN: 2456-7043

(Past name: British Microbiology Research Journal, Past ISSN: 2231-0886, NLM ID: 101608140)

Physicochemical and Microbiological Qualities of Water and Soil Samples from Groundnut Oil Producing Industry

C. A. Osunla^{1,2,3*}, A. Bello¹, D. O. Adejoro¹ and O. A. Makinde¹

¹Department of Microbiology, Adekunle Ajasin University, Akungba Akoko, Ondo State, Nigeria. ²SAMRC Microbial Water Quality Monitoring Centre, University of Fort Hare, Private Bag X1314, Alice 5700, South Africa.

³Applied and Environmental Microbiology Research Group (AEMREG), Department of Biochemistry and Microbiology, University of Fort Hare, Alice 5700, South Africa.

Authors' contributions

All authors contributed to the work presented in this paper. Authors AB executed the research and collated the data. Authors DOA and OAM drafted the first manuscript. Author CAO supervised the research and interpreted the data. Author CAO conceptualized and prepared the final manuscript draft. All authors read and approved the final manuscript.

Article Information

DOI: 10.9734/MRJI/2017/26264

Editor(s)

(1) Laleh Naraghi, Plant Disease Research Department, Iranian Research Institute of Plant Protection, Tehran, Iran.

Reviewers:

(1) Akinnawo Solomon, Federal University of Technology, Nigeria.

(2) Seema A. Belorkar, Bilaspur University, Bilaspur, India. Complete Peer review History: http://www.sciencedomain.org/review-history/19752

Received 7th April 2017 Accepted 17th June 2017 Published 28th June 2017

Original Research Article

ABSTRACT

Triplicate tap and wastewater samples collected from a groundnut oil producing industry in Akure metropolis, Southwest Nigeria were analysed for physicochemical and microbiological qualities using standard procedure. Adjoining soil samples were aseptically collected and serially diluted for total coliform counts using most probable number method. The range of the physicochemical qualities of the tap water and wastewater are as follows: pH (5.7-6.8), colour (4.98-90.0 HU), nitrite (1.6-20.0 mg/l), alkalinity (0.02-52.0 mg/l), BOD (1.79-2.87 mg/l) and TDS (1.59-33.0 mg/l); while for the soil samples, they are as follows: pH (6.7), alkalinity (32 mg/l), nitrate (9.98 mg/l), phosphate (15 mg/l) and total organic carbon (2.74 mg/l). Total coliforms ranged in the order of 10⁴ to 10⁵ cfu/ml and 10⁴ to 10⁵ cfu/g for tap water and soil samples respectively. The bacterial pathogens recovered from the water and soil samples include: *Escherichia coli*, *Klebsiella* spp., *Pseudomonas* spp.,

Bacillus spp., Proteus spp., Shigella spp., Enterobacter spp., Staphylococcus aureus, Streptococcus spp. and Salmonella spp., while the fungal isolates included Fusarium, spp., Aspergillus spp. and Penicillium spp. We conclude that the groundnut wastewater is important point sources of pollution in surface water with potential public health and ecological risks.

Keywords: Wastewater; groundnut; physicochemical properties; bacteria.

1. INTRODUCTION

Freshwater resource is a scarce and unevenly distributed resource, with no direct relation to the development patterns of human societies. Water is crucial for all aspects of life, as it is essential for domestic, recreational and industrial purposes and has become a source of economic and political power [1]. Ninety seven and a half per cent (97.5%) of all water is found in the oceans; of the remaining freshwater only one percent (1%) is available for human's domestic and industrial needs [2]. A healthy and functional aquatic ecosystem provides us with a myriad of services which range from food, medicines, recreational facilities, and waste management [3].

Groundnut oil producing industries, like other industry, make use of water on a daily basis and generate wastewater that are either treated or untreated before being discharged into the environment. According to the [4], partially or untreated effluents can be a source of pollution, a hazard for the receiving waterbodies and all ecosystems that depend on environment. Wastewater can be contaminated with an array of constituents: pathogens, organic compounds, synthetic chemicals, organic matter and heavy metals. They are either in solution or as particulate matter and are carried along in the water from different sources thus impacting water quality [5]. These constituents of wastewater can have cumulative, constant and synergistic characteristics that are capable of affecting the ecosystem health and function, human and animal health, and food production and security [6,7]. This research was designed to reveal the impact of partially and untreated effluents from a groundnut oil processing industry in Akure metropolis, Nigeria, on the physicochemical and microbiological properties of the receiving water bodies.

2. MATERIALS AND METHODS

2.1 Samples Collection

The following samples were randomly and aseptically collected from a groundnut oil

producing industry in Akure, South-western Nigeria: water sample from the source, wastewater generated from the industry and adjourning soil sample. The samples were randomly collected. The water from the source was from a running tap, the wastewater sample was collected against the flow of water with sterile bottle according [8] and the adjourning soil was collected along the surface of the running wastewater and immediately transported to the laboratory for further physicochemical and microbiological analyses.

2.2 Physicochemical Analysis

Physicochemical analysis of parameters such as pH, temperature, colour and odour were carried out in situ. The samples were immediately placed in a lightproof insulated box containing ice-packs and transported to Microbiology laboratory at the Adekunle Ajasin University, Akungba-Akoko through a journey of about 2 h. Upon arrival, the samples were immediately stored at 4℃ until processing. Analysis of water-quality parameters which includes: total dissolved solids (TDS, mg/L), nitrate (NO₃, mg/L), phosphate (mg/L), total suspended solids (TSS, mg/L), biochemical oxygen demand (BOD, mg of O₂/L), chemical oxygen demand (COD, mg of O₂/L), and total solids (TS, mg/L) were carried out using standard methods of [9].

2.3 Culture Media

The culture media used for this research work were Nutrient Agar (NA), Eosin Methylene Blue Agar (EMB), MacConkey Agar (MAC) for bacterial analysis and Potato Dextrose Agar (PDA) for fungal analysis. The media were prepared and sterilized according to the manufacturer's specification.

2.4 Isolation and Identification of Microorganisms

Ten (10) grams of each soil sample was diluted in 90ml of sterile distilled water in a conical flask to get the aliquot, and a tenfold serial dilution was carried out. Ten (10) ml of the water samples were also serially diluted up to dilution factor of 10⁻⁶. An aliquot of 1ml from selected dilutions of each sample was inoculated aseptically into labelled triplicate agar plates of the media (NA, MAC, EMB) using standard pour plate method and incubated at 37°C for 24 -48 hours; Potato Dextrose Agar incubated at room temperature for 5 days for the isolation of fungi. The cultural characteristics observed include shapes, surface, elevation, edge and colour of the microbial growth. Microbial colonies were counted and recorded. Presumptive isolates were preserved on appropriate agar slants stored at 4℃ for further analysis. Presumptive isolates were further characterized and identified using cultural and morphological characteristics as well as biochemical tests.

2.5 Identification of Fungi Isolates

Identification of fungal isolates was done using lactophenol in cotton blue stain. The stained slides were examined with the aid of a microscope, focused with ×10 objective and viewed with ×40 objective lens as described by [10]

3. RESULTS

The results of the physicochemical parameters of the studied samples are shown in Table 1. The pH of the tap water, wastewater and soil samples was 5.70, 6.79 and 6.73 respectively. Tap source had an alkalinity value of 52.02 mg/l, the wastewater had 0.02 mg/L while the adjoining soil had 32.0 mg/L. Wastewater had the highest nitrate present (19.98 mg/L) while the tap water had the lowest nitrate value (1.60 mg/L). Tap

water had the lowest total dissolved solids was 1.59 mg/L while the wastewater highest was 32.99 mg/L. The colour of the tap water was the lowest (4.98 HU) while wastewater had the highest value (89.99 HU). The biological oxygen demand (BOD) for tap water and wastewater ranged from 1.79 mg/L to 2.87 mg/L. There was significant difference between the values of physicochemical parameters observed in studied tap water, wastewater and soil sample at P \leq 0.05.

Table 2 shows the microbial loads of the water samples. The mean Escherichia coli, total coliforms and total viable bacteria count exceeded the acceptable limit for the tap water and adjoin soil samples. The wastewater had the highest total viable bacteria count being too numerous to count with lowest count being 9.0x10⁴ cfu/ml (water source). The total coliform counts for tap water and wastewater ranged were 7.0×10^4 cfu/ml and 3.0×10^6 cfu/ml respectively. The highest Escherichia coli were observed in wastewater (2.9x10⁶ cfu/ml) and adjoining soil (3.8 cfu/g). Tables 3 shows the occurrence of bacterial isolates from tap water, wastewater and adjoining soil samples. Bacteria isolated from these samples Escherichia coli, Pseudomonas species, Bacillus species. Proteus vulgaris. Shigella species. Enterobacter aerogenes, Staphylococcus species. Klebsiella species. Streptococcus species and Salmonella species. The fungal counts are as presented in Table 4. Different species of fungi obtained on Potato Dextrose Agar included: Penicillum spp., Aspergillus spp and Rhizopus spp.

Table 1. Physicochemical analysis of tap water, wastewater and adjoining soil

Parameter	Tap Water	Wastewater	Adjoining soil
рН	6.79 ± 0.03	5.70 ± 0.03	6.73 ± 0.09
Total Dissolved Solids (mg/l)	1.59 ± 0.02	32.99 ± 0.02	NA
Colour (Hazen Unit)	4.98 ± 0.02	89.99 ± 0.01	NA
Alkalinity (mg/l)	52.02 ± 0.02	0.02 ± 0.01	32.00 ±0.04
Nitrate (mg/l)	1.60 ± 0.03	19.98 ± 0.02	9.98 ± 0.06
Phosphate (mg/l)	NA	NA	14.99 ± 0.02
Total Suspended Solids (mg/L)	3.97 ± 0.02	1.10 ± 0.03	NA
Biochemical Oxygen Demand (mg/L)	1.79 ± 0.02	2.87 ± 0.54	NA
Total Organic Carbon (%)	NA	NA	2.74 ± 0.02
Lead (mg/L)	NA	NA	0.98 ± 0.02
Copper (mg/L)	0.02 ± 0.01	0.10 ± 0.01	0.09 ± 0.03

Key: NA- Not applicable

Table 2. Total bacterial counts on different media

Sample	NA	EMB	MAC
Tap water	9.0 x 10 ⁴	5.0 x 10⁴	7.0 x 10 ⁴
Wastewater	TNC	2.9 x 10 ⁶	3.0×10^6
Adjoining soil	3.2×10^6	3.8×10^6	2.8×10^6

Key: NA = Nutrient agar, EMB = Eosin methylene blue agar

MAC = MacConkey agar, TNC = Too numerous to

Table 3. Bacterial Isolates From tap source, wastewater and adjoining soil samples

Bacterium	Tap Water	Waste -water	Adjoining soil
Bacillus spp	-	+	+
Enterobacter	-	+	+
aerogenes			
Escherichia coli	+	+	+
Proteus vulgaris	-	-	+
Pseudomonas	-	+	+
spp			
Salmonella spp	-	+	+
<i>Shigella</i> spp	-	+	+
Staphylococcus	+	+	+
aureus			
Staphylococcus	-	+	+
spp			
Streptococcus	-	-	+
spp			

Key: + = Present, -= Absent

4. DISCUSSION

microbiological physicochemical and parameters of the tap water, wastewater and adjourning soil of a groundnut oil producing industry were evaluated in this study. Physicochemical analysis of the wastewater revealed that the pH was 5.70 with a strong choking odour emitted. Biological oxygen demand (BOD) concentrations of the tap water and wastewater were observed to be low. However, it must be noted that BOD usually becomes problematic when it becomes higher than 5 mg/L and especially when it is in combination with large volume of total dissolved solids, which could lead to clogging of soil [11]. It been reported that each of physicochemical parameters analysed has synergetic effects on the others, which has some impact on water quality, as well as the use of the water [12]. The level of total solids in the

wastewater is most probably due to the presence of spent groundnut particles and high dissolved organic matter content of the wastewater from the industry. The mean value of total dissolved solids of the discharged effluent was much lower than the stipulated limit of 2000 mg/L [13]. Elevated levels of nitrates can result in eutrophication, giving rise to increase algae growth and eventually leading to reduced dissolved oxygen levels in the water [14].

In rural areas of developing countries, the great majority of health-related water quality problems are the result of bacteriological or other biological contamination. The presence or abundance of faecal coliform in wastewater final effluents is a feeble index of the presence of human pathogens in wastewater entering environmental waters. Regardless of this, utilization of faecal coliforms for water quality testing purposes is universal [15]. The presence of high counts of enteric bacteria suggests the possible presence of potential pathogens in the tap water, and in this regard the effluent and tap water poses a serious threat to the receiving waterbodies and its entire ecosystem. In a study by [16], it was demonstrated that these enteric microorganisms are of huge public health concern, and as such water containing them must be treated properly before use or before being discharged into the environment. The high enteric bacterial counts indicate poor sanitary and unhygienic practices in the industry's environment, and this poses risk to the final product and receiving water bodies around the industry. The presence of bacterial species such as Escherichia, Pseudomonas and Streptococcus in some of the cultured samples indicates a contamination which may be related human and animal activities in the environment and mostly from faecal origin. The presence of Staphylococcus aureus in the water source could be attributed to the improper handling from workers, as S. aureus is a normal flora of the human skin and mucosal membranes [17]. This poses a serious public health hazard, capable of causing water-borne diseases outbreaks. In a study carried out by [18], the authors established the tendency of enteric pathogens moving from surface to the underground water, and emphasised the importance of the intensity of water flow and the number of water applications to the movement. Therefore, improper discharge of this wastewater could lead to contamination of underground water.

Table 4. Total Fungal Count and morphological characteristics

Plate	Number of colonies on plate (cfu/g)	Shape of colonies	Colour of colonies
FA ₁	2×10^2	Oval, irregular	Brown, creamy
FA_2	1 x 10 ³	Round, circular	Black
FB_1	9×10^2	Circular, regular	Creamy, yellowish, brown
FB_2	7×10^3	Oval, circular	Brown, black
FAs ₁	5×10^2	Circular, round	White, black underlay
FAs_2	4×10^3	Irregular	White, black
Control	0	No growth	No colour

Key: FA = Water source fungi, FB = Wastewater fungi, FAs = Soil fungi

5. CONCLUSION

The ongoing problems facing the water and sanitation body in Nigeria is still a major public health threat; dearth of access to portable water, waterborne diseases and faecal pollution to freshwater highlight the need for the Nigeria sanitation agency to begin to revise current guidelines to meet acceptable standards set by other developed nations. The groundnut oil industry fared poorly in the treatment of its wastewater, and this result reveals the severe pollution resulting from the elevated levels of organic nutrients in the final effluent. The noncompliance of the groundnut oil processing industry presents it as a plant that poses a potential danger to public health. Thus the outcome of this study definitely suggests an urgent need for pollutant reduction inputs into surface water and the need to upgrade existing wastewater management regulations.

DISCLAIMER

Some part of this manuscript was previously presented in the following conference.

Conference name: South African Society for Microbiology (SASM).

Dates: 17-20 January 2016.

Location: Coastlands, Umhlanga, South Africa Web Link of the proceeding: http://ddt72ar9zv4px.cloudfront.net/wp-content/uploads/2016/01/SASM-2016-Poster-Abstracts1.pdf

COMPETING INTERESTS

Authors have declared that no competing interests exist.

REFERENCES

 Narasimhan TN. Water, law, science. Journal of Hydrology. 2008;349(1-2):125-138.

- 2. Upadhyay M, Bareth S. Study of physicochemical properties of surface water (Hasdeo River and ponds) in Champa and Janjgir region. International Journal of Current Pharmaceutical and Clinical Research. 2014;4(2):126-128.
- Corcoran E, Nellemann E, Baker R, Bos D, Osborn H, Savelli (eds). Sick water? The central role of wastewater management in sustainable development a rapid response assessment. United Nations Environment Programme, UN-Habitat, GRID-Arendal; 2010.

Available: www.grida.no (Retrieved 26th September, 2015).

- Millennium ecosystem assessment. Millennium ecosystem assessment, concepts of ecosystem value and valuation approaches. Island Press, Washington, DC: 2005.
- Techobanoglous G, Burton FL, Stensel HD. Wastewater Engineering: Treatment, Disposal and Reuse. 4th edition. Tata McGraw Hill Publishing. Delhi, India. 2003; 12-23.
- Appelgren B. Water and ethics: Water in agriculture. Series and water and ethics, Essay 5. Published by the United Nations educational scientific and cultural organization 7, Place de Fontenoy. Paris 07 SP (France). 2004;75352.
- 7. Pimentel D, Pimentel M. Food, energy, and society. Boca Raton, Fla., CRC; London: Taylor and Francis (Distributor); 2008.
- 8. Cheesbrough M. Medical Laboratory Manual for Tropical Countries Microbiology. 2006;II:400-480.
- APHA, AWWA, WEF. Standard methods for examination of water and wastewater.
 22nd ed. Washington: American Public Health Association. 2012;1360.
- Alexopoulous CJ, Mims, CW, Black Well MB. Introductory mycology. John Wiley and Sons; 1996.

ISBN: 0-471-52229-5

- Darrell V. Rule development committee issue research report draft, organic loading rates. Tumwater WA, Washington State Department of Health. Wastewater Management Program; 2002.
 Available: http://www.doh.wa.gov/ehp/ts/WW/TechlssueReports/T-3aOrganicLoading-VSD.doc
 (Retrieved 26th September, 2015)
- Akpor O. Wastewater effluent discharge: Effects and treatment processes. Int. Conf. Chem. Biol. Environ. Eng. 2011;20: 85–91.
- FEPA. National guideline and standards for industrial effluents, gaseous emissions and hazardous waste management in Nigeria. Federal Environmental Protection Agency (FEPA) Lagos, Nigeria; 1991.
- Adeyemo OK, Adedokun OA, Yusuf RK, Adeleye EA. Seasonal changes in physico-

- chemical parameters and nutrient load of river sediments in Ibadan city, Nigeria. Global NEST Journal. 2008;10(3):326-336.
- 15. McManus M. Safety of private water supplies. The University of Tennessee Agricultural Extension Service, PB. 1990;1356.
- Ashbolt NJ. Microbial contamination of drinking water and human health from community water systems. Curr. Environ. Health Rep. 2015;2(1):95-106.
- Adams MR, Moss MO. Food microbiology. 4th Edition. New Age International, New Delhi. 2009;188-206.
- Trevors JT, van Elsas JD, van Overbeek LS, Starodub ME. Transport of a genetically engineered Pseudomonas fluorescens strain through a soil microcosm. Applied and Environmental Microbiology. 1990;56:401-408.

© 2017 Osunla et al.; This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Peer-review history:
The peer review history for this paper can be accessed here:
http://sciencedomain.org/review-history/19752